



Contribution ID: 144

Type: Contributed poster

## WAVEGUIDE LASER BASED ON MESOSCOPIC ORDERED HYBRID TITANIA AND SILICA SOL-GEL FILMS

*Monday, 25 June 2018 18:45 (15 minutes)*

Nanoscale hybrid films manifest a set of properties that can be beneficial when used in dye lasers, amplifiers, switching devices, solar cells, OLEDs. Studies on the fabrication of sol-gel optical hybrid SiO<sub>2</sub> and TiO<sub>2</sub> films for photovoltaic devices or planar optical waveguide are continuously gaining attention over the years because these materials have numerous applications in the field of microelectronics and optoelectronics. We have studied the characteristics of thin hybrid films which could be useful to tune the quality of mesoscale surface and developed the self-assembly approach based on the sol-gel method to fabricate high-quality hybrid nanocomposite films using network-forming oxides such as silica or titanium [1-2]. In the frame of given approach the optically transparent, low roughness hybrid silicate and titanium films of the nanoscale thickness have been manufactured and have been studied their luminescence property in the broad concentration range [3]. This property of the nanoscale hybrid films was the one of reason to harness them as laser media [4]. The main target of our work was consisted in studying planar waveguide lasing based on the structured hybrid films at its nanoscale thickness. For both films, we observed lasing, which appears as a radiation of the central beam due to the enhanced luminescence (along with the track) and a lasing that occurs due to the distributed grating feedback of the enhancement created by the oncoming waves of the enhanced luminescence. In case of a TiO<sub>2</sub> film, it was found that the radiation that emerges from the strip ends sharply with a narrow spectrum under pumping above 0.2 MW/cm<sup>2</sup> what is close to the lasing spectrum of the conventional dye laser. The observed narrow directivity in a transverse direction is very surprising because the diffraction should cause this directivity to be much wider. One possible explanation of the narrow directivity is the formation of a thermal lens caused by the transversal temperature gradient. Our estimations show that the thermal lensing may be effective for thin films even for the low intensity lasers. These results show a possibility for a high-quality lasing on the basic mode of a waveguide that forms the central beam.

1. A. Kazakevičius, D. Peckus, L. Valkunas, E. Leonenko, G. Telbiz and V. Gulbinas *Journal of Phys. Chem. C*, 119 (2015) 19126–19133.
2. G. Telbiz, S. Bugaychuk, E. Leonenko, L. Derzhypolska, V. Gnatovskiy, *Nanoscale Research Letters*, 10:196 (2015) 1-7.
3. G. Telbiz, E. Leonenko, M. Dvoynenko, *Mol. Cryst. Liquid Cryst.*, 642 (2017) 74-80.
4. E. A. Tikhonov, V. P. Yashchuk and G. M. Telbiz, *Laser Phys.*, 28 (2018) 045801 (7pp)

**Primary authors:** Dr TELBIZ, German (L.V. Pisarzhevskii Institute of Physical Chemistry, National Academy of Sciences of Ukraine); Dr LEONENKO, Eugen (L.V. Pisarzhevskii Institute of Physical Chemistry of the National Academy of Sciences of Ukraine); Dr YASHCHUK, Vasyl (Kyiv T. Shevchenko National University); Dr KUKHTAREV, Nikolai (Alabama A&M University); Dr TIKHONOV, Eugene (Institute of Physics); Dr KULIK, Tetiana (Chuiko Institute of Surface Chemistry of National Academy of Sciences of Ukraine)

**Presenter:** Dr KULIK, Tetiana (Chuiko Institute of Surface Chemistry of National Academy of Sciences of Ukraine)

**Session Classification:** Poster session